(12) PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 200244365 B2
(10) Patent No. 776816

(54) Title
Method and apparatus for delivering aerosolized medication

(51)6 International Patent Classification(s)
A61M 015/00

(21) Application No: 200244365 (22) Application Date: 2002.05.23

(43) Publication Date: 2002.07.11
(43) Publication Journal Date: 2002.07.11
(44) Accepted Journal Date: 2004.09.23

(62) Divisional of:
199910847

(71) Applicant(s)
Systemic Pulmonary Delivery, Ltd.

(72) Inventor(s)
Thomas Alex Armer; Bryce Burwick Evans; Nahed Mohsen Mohsen; Richard Matthew Pavkov; Atul M. Sudhalkar

(74) Agent/Attorney
E F Wellington and Co,312 St Kilda Road,MELBOURNE VIC 3006

(56) Related Art
US 5060643

ABSTRACT

Method and apparatus for delivering aerosolized medication employing a variable-volume device and a container retention.

AUSTRALIA

PATENTS ACT 1990

REGULATION 3.2

Name of Applicant: SYSTEMIC PULMONARY DELIVERY, LTD.

Actual Inventors: THOMAS ALEX ARMER, BRYCE BURWICK EVANS, NAHED MORSEN MOHSEN, RICHARD MATTHEW PAVKOV AND ATUL M. SUDHALKAR

Address for Service: E.F. WELLINGTON & CO., Patent and Trade Mark Attorneys, 312 St. Kilda Road, Melbourne, Southbank, Victoria, 3006.

Invention Title:

"METHOD AND APPARATUS FOR DELIVERING AEROSOLIZED MEDICATION",

Details of Associated Provisional Applications Nos:

The following statement is a full description of this invention including the best method of performing it known to us.

METHOD AND APPARATUS FOR DELIVERING AEROSOLIZED MEDICATION

Field of the Invention

The present application, which is a divisional application derived from Application No. 10847/99, relates to methods and apparatus for delivering a dose of aerosolized medication for inhalation by a patient into the lungs.

Background of the Invention

Aerosols are increasingly being used for delivering medication to the pulmonary structures of the lungs. For example, in the treatment of asthma, inhalers are commonly used for delivering bronchodilators such as β_2 agonists and anti-inflammatory agents such as corticosteroids. Two types of inhalers are in common use, metered dose inhalers (MDIs) and dry powder inhalers (DPIs). Both types have as their object the delivery of medications, which is typically in the form of a solid particulate or powder, into the airways of the lungs or the location of the medical being treated.

In the MDI device, the medication is provided by the pharmaceutical manufacturer in a pressurized vessel container, with the medication being suspended

or dispersed in a liquid propellant such as a chlorofluorocarbon (CFC) or hydrofluoroalkane (HFA). The canister includes a metering valve having a hollow discharge stem which can be depressed toward into the canister to discharge a metered volume of propellant-medication mixture in the form of an aerosol comprising fine droplets of propellant in which particles of the medication are suspended or dissolved. A typical MDI for use with such a canister includes a housing having an actuator and nozzle. The canister is inserted into the housing with the hollow discharge stem of the canister being received in a bore in the actuator. Depressing the closed end of the canister causes the stem to be pushed inward into the canister so that a metered volume of medication is discharged through the nozzle. The housing further defines a downcomer in fluid communication with the nozzle, the downcomer having an outlet at a mouthpiece portion of the housing, such that the aerosolized medication may be inhaled after it exits the mouthpiece portion. The patient either ignores the mouthpiece and sprays with the lips closed around the mouthpiece, or holds the mouthpiece at a slight distance away from an open mouth. The patient then depresses the canister to discharge the medication, and simultaneously inhales.

Existing MDIs suffer from a number of significant disadvantages. One problem with existing MDIs is poor delivery efficiency of the medication. It has been estimated that on average, with existing MDIs, only about 10 percent of the

medication dose which is dispensed from the canister actually reaches the lungs where it can achieve the intended result.

Poor delivery efficiency is caused by a number of factors. One of these is immediate evaporation of propellant, resulting in a large portion of the metered dose being delivered in a form which cannot be inhaled into the lungs. For effective delivery of aerosolized medications to the alveoli of the lungs, it is desirable that most of the particles which are inspired be less than about 10 microns (one micron=one-thousandth of a millimeter) in size, and preferably between about 1 microns and 5 microns. Immediate evaporation of propellant at the outlet of the mouthpiece results in a substantial fraction of the metered dose being delivered in the form of relatively large liquid droplets instead of fine dry particles and/or vapor. Such droplets cannot be inspired, but rather tend to impact the inside of the mouth and at the back of the patient's throat, with the result that much of the medication is swallowed. The local concentration of medication in the mouth and throat can cause local irritation-appreciation response, as well as development of fungal infections in the case of corticosteroids. Additionally, swallowing ill, spoiled causes relaxation of the smooth muscles of the gastrointestinal tract, which decreases contractility and activity of the stomach. Further, the wasted medication has been estimated to cost U.S. patients about $700 million per year.

Another factor contributing to the problem of poor delivery efficiency is high flower velocity of the aerosol as it exits the mouthpiece, which tends to lead to

impaction of the aerosol in the mouth and throat. Ideally, the velocity of the aerosol should match the velocity of the patient's inspired breath so that the particles are carried in the breath and carried into the lungs. With many existing MDIs, the exit velocity of the aerosol substantially exceeds the velocity of the patient's breath. The high-velocity plume strikes the back of the throat, causing impaction and sticking.

Yet another factor contributing to the poor delivery efficiency of existing MDIs is excessive length of the plume or bolus of aerosol exiting the device. In existing MDIs, this length typically exceeds 20 centimeters, which makes it difficult for the patient to inhale the entire bolus.

In an effort to decrease plume velocity, most MDI designers have added volume spacers between the aerosol nozzle and the mouthpiece. Although spacers improve delivery efficiency, some of the drug which is discharged from the nozzle impacts and sticks on inner surfaces of the spacer, and is therefore unavailable for inhalation by the user. Thus, MDIs with spacers still suffer from unacceptably low delivery efficiencies.

Furthermore, although dry powder inhalers inherently avoid some of the aforementioned problems of MDIs, such as excessive aerosol velocity, DPIs still suffer from the problems of impaction and sticking of medication on the inner surfaces of the device, particularly under certain environmental conditions such as high relative humidity, which tends to cause particle aggregation.

Another problem with existing MDIs is the difficulty patients have in coordinating their inhalation with the discharge of the aerosol. In manually operated MDIs, patients frequently inhale too early or too late to effectively inspire the medication. Although a number of breath-actuated MDIs have been devised to address this problem, most of these devices cause discharge at the very onset of the patient's inspiratory effort. Depending on the drug medication being aerosol and its location, it may often be more desirable for the medication to be discharged near the peak of the patient's inhalation rather than the beginning. Further, it may be desirable to be able to selectively vary the point in the patient's inhalation at which medication is discharged in order to affect the location of drug delivery in the medication being aerosol. These advantages are not possible with existing MDIs.

Accordingly, it has been an object of the present invention to provide a method and apparatus for delivering an aerosolized medication in which the respirable fraction of the aerosol dose (i.e., the fraction in the form of dry particles of the optimum size) is maximized at the exit of the apparatus.

It has been a further object of the present invention to provide a method and apparatus for delivering an aerosolized medication in which the flower velocity of the aerosol at the exit of the apparatus approximately matches the velocity of the patient's inspired breath.

It has been another object of the invention to minimize deposition and sticking of the drug particles in the form of an aerosol within an inhaler apparatus.

It has been a still further object of the present invention to provide a method and apparatus for delivering an aerosolized medication to which the length of the tubing of aerosolized medication which exits the apparatus is as short as possible.

A further object of the invention has been to provide a method and apparatus for standardizing the preparation of liquid propellant in an inhaler.

Still another object of the invention has been to provide a method and apparatus for delivering an aerosolized medication in which inspection and sticking of medication on the inner walls of the apparatus is minimized.

It has been another object of the present invention to provide a method and apparatus for delivering an aerosolized medication in which the discharge of medication is synchronized with the patient's inspired breath, and in which the timing of the discharge in relation to the patient's breath can be relatively varied.

Summary of the Invention

The above and other objects of the invention are achieved by the methods and apparatus of the invention in which flow control techniques and devices are used to promote mixing of the propellant-medication mixture with air at increased evaporation of propellant, to slow down the aerosol plume before it reaches the exit of the apparatus, and to reduce the impaction of aerosol on the inner walls of the apparatus. The invention also provides an apparatus and method for synchronizing the actuation of the medicine with the patient's inspiratory effort created on the mouthpiece of the apparatus.

More specifically, the invention provides a aerosol drug inhaler apparatus including a housing adapted to support a pressurized canister, the housing having an actuator and nozzle assembly with a bore adapted to receive the hollow outlet stem of the canister, the housing further including a generally tubular enclosure having an open end forming a mouthpiece adapted to be inserted into the mouth of a user, a nozzle discharge orifice of the actuator and nozzle assembly being positioned to direct a plume of aerosolized medication into the enclosure and an air tube supported within the enclosure and having an air tube outlet arranged opposite the nozzle discharge orifice and an air tube inlet in fluid communication with ambient air outside the enclosure, the air tube being arranged so that air flowing out of the air tube outlet is directed so as to impinge on a plume of aerosolized medication discharged from the canister through the nozzle discharge orifice. Thus, an inspiratory effort created on the mouthpiece causes air to flow into the air tube inlet and out the air tube outlet to impinge on the plume and thereby enhance dispersion and mixing of the medication within the enclosure. The air jet from the air tube also causes the plume to slow down so that the velocity of the aerosol exiting the device approximately matches the velocity of a patient's inspired breath. Slowing down the plume also increases the residence time of the aerosol within the apparatus and tends to a shower baths to be inhaled. The increased mixing and residence time promote more complete evaporation of propellant at the exit of the mouthpiece.

In one embodiment of the invention, the apparatus is configured so that the nozzle discharge orifice directs a plume toward the open end of the mouthpiece. The air tube is arranged to direct an air jet away from the open end of the mouthpiece so as to impinge on the plume. The air tube is supported within the enclosure by one or more hollow spokes connected to the wall of the enclosure, with the hollow passage of each spoke being connected at one end to a corresponding passage through the enclosure wall to ambient air outside the enclosure and at the other end to the inlet of the air tube. When the patient inhales on the open end of the mouthpiece, air is drawn into the air tube to create an air jet to exit the air tube. Once this air jet has been established, the canister is actuated to discharge a plume of aerosol toward the air jet. The plume and air jet cross, causing mixing and deceleration of the plume.

In another embodiment of the invention, the nozzle is positioned to direct a plume away from the open end of the mouthpiece toward the far end of the enclosure, which end is substantially closed by an end wall. The air tube is mounted near the end wall, with the inlet of the air tube connected to a passage through the end wall to ambient air outside the enclosure. Inhalation by a patient on the open end causes air to be drawn through the air tube in a direction toward the patient's mouth. Once the air jet from the air tube has been established, the canister is actuated to direct a plume toward the closed end of the enclosure. The air jet and plume cross, causing mixing and deceleration of the plume. The plume then reverse direction before

exiting the mouthpiece, so that the same length of conduit is used twice, thereby further increasing residence time of the aerosol within the device.

To reduce impaction and sticking of medication on the inner walls of the apparatus, the invention provides an aerosol flow control apparatus, useful for older MDI or DPI devices, including a housing defining a conduit, the conduit having an open end defining a mouthpiece and a substantially closed end defined by an end wall remote from the mouthpiece, with a medication dispenser assembly being arranged within the housing to direct medication into the conduit. The medication dispenser may be a pressurized canister with actuator and nozzle, or alternatively may be a dispenser for medication in dry powder form. The end wall includes a plurality of auxiliary air inlets in fluid communication with ambient air outside the conduit, the auxiliary air inlets opening into the conduit adjacent the inner wall of the conduit, in a direction generally toward the open end of the mouthpiece. The conduit further includes a plurality of vortex generators mounted on the inner wall thereof downstream of the auxiliary air inlets, the auxiliary air inlets and vortex generators cooperating to establish a turbulent air flow along the inner wall of the conduit upon an inspiratory effort being created on the mouthpiece. The auxiliary air flow acts as a buffer or boundary layer flow along the inner walls of the conduit, reducing the likelihood of aerosol droplets or any particles impacting and permanently sticking to the inner walls. The vortex generators preferably comprise inwardly directed vanes

which are arranged at an angle to the axial direction so as to impart swirl and vorticity to the air flowing over them.

The inhaler further provides an aerosol flow control apparatus for use with a pressurized canister of medication, in which discharge of the aerosol plume is caused by the patient's inspiratory effort, with the timing of the discharge in relation to the inhalation being relatively variable. To these ends, the apparatus includes a housing adapted to support the canister between a first position in which the discharge stem of the canister is in an inoperative position to a second position in which the discharge stem is in an operative position for discharging a metered volume of medication, the housing further including an outlet through which a user can inhale, the outlet defining a primary air passage. A canister restraint is arranged in the housing and is movable from a rest position in which relative movement between the canister body and discharge stem is prevented to a discharge position in which such movement is permitted. The canister restraint forms a part of, or alternatively is coupled to, a device such as a bellows or a movable displacer plate assembly which defines a variable-volume chamber. The inhaler includes a mailbox member which urges the canister into the second position upon movement of the canister restraint into its discharge position. A secondary air passage extends through the housing between the primary air passage and ambient air outside the housing, the secondary air passage including a venturi. The variable-volume chamber is in fluid communication with a throat of the venturi, whereby inhalation of a user through the

outlet creates a low pressure in the venturi throat so as to evacuate air from the chamber and thereby cause the canister restraint to move into the discharge position. By appropriate selection of design parameters such as the chamber cross-sectional area, the force exerted by the mailbox member on the canister, the venturi size, and the secondary air passage dimension, the device can be designed to cause actuation of the canister near the peak of a patient's inspiratory effort.

The device preferably further includes means for selectively varying the timing of actuation. For instance, the device may include an adjustment screw controlling how the secondary air passage is set as a variable flow restriction. Turning the screw one direction increases the amount of flow restriction, such that for a given inspiratory rate through the canister, the amount of time required to evacuate the chamber sufficiently to cause actuation is increased. Conversely, turning the screw in the opposite direction decreases the amount of time required to cause actuation.

These and other objects and advantages of the present invention shall become more apparent from the accompanying drawings and the description thereof.

Brief Description of the Drawings

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate various embodiments of the invention and, together with the general description of the invention given above and the detailed description given below, serve to explain the principles of the invention.

FIG. 1 is a perspective view of an inhaler in accordance with the principles of the present invention.

FIG. 2 is an exploded view of the inhaler of FIG. 1.

FIG. 3 is a cross-sectional view of the inhaler taken along lines 3-3 of FIG. 1.

FIG. 3A is a partial cross-sectional view showing an alternative embodiment of the actuator and nozzle of the inhaler.

FIG. 4 is a cross-sectional view similar to FIG. 3, showing an alternative embodiment of the inhaler.

FIG. 5 is a cross-sectional view similar to FIG. 3, showing yet another alternative embodiment of the inhaler.

FIG. 6 is cross-sectional view of the inhaler of FIG. 5 taken on a plane normal to that of FIG. 5.

FIG. 7 is a cross-sectional view of still another alternative embodiment of the invention, having features for achieving automatic actuation of a canister responsive to a patient's inspiration through the inhaler.

FIG. 8 is a perspective view of the trigger which engages and disengages the canister in the inhaler of FIG. 7.

FIG. 9 is side cut-away view, partly in cross-section, of yet another embodiment of the invention, showing an alternative arrangement for achieving automatic actuation of a canister responsive to a patient's breath.

Detailed Description of the Drawings

FIGS. 1-3 depict a first embodiment of an inhaler 10 in accordance with the principles of the invention. The inhaler 10 includes a housing 12 which has a receptacle portion 14 communicating with a mouthpiece 16. The receptacle portion 14 is in the form of a sleeve adapted to receive a standard pressurized canister 18 containing a medication. The canister 18 forms no part of the present invention. The inhaler apparatus of the present invention is usable with any standard pressurized canister having an internal metering valve with a hollow discharge stem which may be depressed inwardly with respect to the canister body from an inoperative position in which discharge of medication is prevented, to an operative position in which a metered volume of the canister contents is discharged through the hollow discharge stem.

The mouthpiece 16 includes an open end 20 spaced from the receptacle portion 14, and a closed end 22 defined by an end wall 24 which is connected to the receptacle portion 14. The end wall 24 preferably is generally conical or hemispherical in shape, with an apex of the end wall 24 directing the portion of the end wall 24 furthest from the open end 20.

With reference to FIG. 3, the housing 12 further includes an actuator and nozzle assembly 25 supported by the end wall 24. The actuator and nozzle assembly 25 includes a boss 27 which is adapted to receive the hollow discharge stem (not shown in FIGS. 1-2) of the canister 18, and a nozzle discharge orifice 30 in fluid

concentricities with the bore 23. The nozzle discharge orifice 30 is advantageously located in the open end 24 and arranged to direct an annular plume generally along the central longitudinal axis 32 of the conduit. The orifice 30 preferably has an internal diameter at the exit of less than about 0.025 inch, and more preferably between about 0.005 inch and about 0.015 inch.

Thus, upon the container 12 being depressed in the downward direction in FIG. 1, a metered volume of medication will be discharged into the bore 23 and out the orifice 30 to form a generally conical plume of aerosolized medication within the conduit 16, directed generally toward the open end 20 thereof. The inhaler 10 includes features which promote dispersion and mixing of the aerosolized medication with air within the conduit to enhance evaporation and decrease the velocity of the liquid propellant discharged from the container 12. More specifically, the inhaler 10 includes an air tube 34 supported within the conduit 16. The air tube 34 has an entry 36 which is spaced downstream of and in opposing relationship with the nozzle discharge orifice 30, and an inlet 38 which is in fluid communication with ambient air outside the conduit 16. In the embodiment shown in FIGS. 1-3, the air tube 34 is a hose tube which has a generally axial portion 40 which is generally aligned along the conduit's longitudinal axis 32, and a generally radial portion 42 which is attached to the inner wall 44 of the conduit 16. When a user exerts an inspiratory effort on the open end 20 of the conduit 16, air is drawn into outside the conduit 16 into the air tube inlet 38, making the air tube entry 36 in a direction toward the nozzle discharge

orifice 30. The portion 40 of air tube 34 is located and oriented within the conduit 16 so that air flowing out from the entry 36 will impinge on a plume of aerosol exiting the nozzle orifice 30. Once this air flow from the tube 34 has been established, the entering valve of the canister 12 is actuated to discharge a plume of aerosolized medication from the orifice 30. The impingement of air from air tube 34 on the plume causes the plume to slow down and be dispersed so as to occupy a larger portion of the cross section of the conduit 16. The result is enhanced mixing of the aerosol with air, which promotes more complete evaporation of liquid propellant by the time the aerosol bolus exits the open end 20 of the conduit 16, and a reduction in velocity of the plume exiting the open end 20 so that it approaches the velocity of the inspiratory breath. Accordingly, a greater fraction of the metered dose of medication dispensed from the container 12 exits the open end 20 in the form of respirable dry particles of the appropriate size of about one to five microns moving at a relatively low velocity that substantially matches the inspiratory breath velocity, as opposed to relatively large liquid droplets moving at a relatively high velocity. Impaction and sticking of medication within the mouth and throat are thereby reduced.

The air tube 34 and conduit 16 can be integrally formed of one piece, with the internal passage of the air tube 34 extending through the conduit 16 to establish fluid communication with air outside the conduit 16. Alternatively, the air tube 34 can be formed of a metal tube bent into the appropriate configuration and attached to the conduit 16 at the inlet end 38.

Although the embodiments illustrated in FIGS. 1-3 and 7 show the air tube 34 bent at an angle of 90 degrees with the portion 40 coaxially aligned with the axis 41 (FIG. 3) of the nozzle orifice 30, other arrangements may be used without sacrificing the advantages of the invention. For example, the portion 40 may be arranged at an obtuse angle (i.e., between about 90 degrees and 180 degrees, 180 degrees being defined as exactly opposite to the direction of a plume exiting the orifice 30) to the axis 41 of the nozzle orifice 30, with the portion 40 of air tube 34 being oriented to direct an air jet at the orifice 30. Additionally, the portion 42 which attaches to the conduit wall need not be radial, but can be oriented at an acute or obtuse angle to the conduit wall 44.

The inhalation further includes features which reduce the likelihood of liquid droplets or dry particles impacting and permanently sticking to the inner walls 24 and 44 of the conduit 16. More particularly, the inhaler 10 includes a plurality of auxiliary air inlets 46 through the end wall 24 and circumferentially spaced therearound at a least one diameter radially from the nozzle orifice 30. A first circumferential ring of auxiliary air inlets 46 are located adjacent the junction 48 between the end wall 24 and the inner wall 44 of the conduit 16. A second circumferential ring of auxiliary air inlets 47 are located radially between the junction 48 and the nozzle orifice 30. An inspiratory effort exerted on the open end 20 of the conduit 16 causes air to flow into the auxiliary air inlets 46 and 47 as indicated by arrows 50, and outward therefrom along the inner wall 44 of the conduit 16 and

outward from end wall 24, as indicated by arrows 52. This auxiliary air flow forms a buffer or boundary layer air flow along the inner wall 44 and end wall 24 which tends to reduce the impaction and permanent sticking of medication on inner wall 44 and end wall 24.

To the further attainment of this end, the inhaler 10 also includes a plurality of vanes projections or vanes 54 (best seen in FIG. 2) contained on the inner wall 44 of the conduit 16 and extending inwardly therefrom. The vanes 54 are located downstream of the auxiliary air inlets 46, with each vane 54 advantageously being located approximately in axial alignment with one of the auxiliary air inlets 46. The vanes 54 are oriented at an angle to the axial direction defined by longitudinal axis 32, so that vorticity and swirl are imparted to air flowing over them. Thus, the boundary layer air flow created by auxiliary air inlets 46 encounters the vanes 54, which impart vorticity and swirl to the boundary layer air flow. This vorticity and swirl further reduces the likelihood of aerosol droplets or particles impacting and permanently sticking to the inner wall 44.

As shown in FIGS. 1 and 3, the inhaler 10 includes a separate mouthpiece 56 which connects to the open end 20 of the conduit 16. The mouthpiece 56 has a reduced diameter portion 58 adapted to be inserted into the mouth of a user of the inhaler 10. After completely exhaling, the user inserts the portion 58 into the mouth with the lips closed around the portion 58, and then begins to inhale, which establishes air flow from the air tube 34 and through the auxiliary air inlets 46. Once

these air flows are coordinated and while maintaining an intimate, the user depresses the cushion 18 to discharge a measured volume of medication and propellant mixture from the nozzle discharge orifice 30. The user continues to inhale to fill the lungs to their capacity, and then typically holds the inhaler for a period of time to allow the aerosolized medication to mix within the airways of the lungs.

As shown in FIGS. 1-3, the housing 12 is formed in four sections (including the mouthpiece 32) which telescopically fit together. However, for ease of manufacturing, the housing 12 may alternatively be formed in fewer than four sections. For example, the housing 12 may be formed in two sections, a first section including the receptacle portion 14, end wall 26, and the conduit 16 up to and including the vanes 24, and a second section including the portion of conduit 16 having the air inlet 34 and the mouthpiece 32. Alternatively, the housing 14 may be formed in two sections split on a longitudinal plane through the conduit, the two sections being generally mirror images of each other which are joined together along the plane of symmetry. Nevertheless, for illustrative purposes, an embodiment having four sections is shown and described.

A first section 60 includes the receptacle portion 14, the end wall 26 and scissor and nozzle assembly 28, and a generally cylindrical portion 62 which forms a part of the conduit 16 and is connected to the end wall 26 at the junction 64. The first section 60 subsequently is integrally formed of one piece, although it may alternately be formed in multiple pieces which are subsequently joined together.

A second section 66 includes a second generally cylindrical portion 66 whose inner and outer diameters are equal to those of the first generally cylindrical portion 62, and a reduced-diameter portion 68 which is telescopingly received within the downstream open end of first cylindrical portion 62. The portion 68 has an inner wall 70 which is generally conical, converging slightly in the axial direction toward the mouthpiece 32. The vanes 24 are mounted on the inner wall 70. Second section 66 preferably is integrally formed of one piece, although it may alternatively be formed in multiple pieces which are subsequently joined.

A third section 72 of the housing 12 includes a third generally cylindrical portion 74 whose inner and outer diameters are equal to those of the second generally cylindrical portion 66, and a reduced diameter cylindrical portion 76 which is telescopingly received within the open downstream end of second generally cylindrical portion 66. The outer diameter of portion 76 is approximately equal to the inner diameter of portion 66 so as to provide a tight fit between these parts. The inner surface 73 of portion 74 has a diameter which is approximately equal to the reduced diameter of the conical inner wall 70 so that the junction between surfaces 70 and 73 does not present any substantial step in the flowpath defined by the conduit 16. The air inlet 34 is mounted on the inner surface of the third section 72 at the junction between the inner surface 73 and the inner surface 70 of third cylindrical portion 74. A hole 52 through the portion 74 mates with the internal passage of air inlet 34 to provide fluid communication between the inlet 34 of air inlet 34 and

inclose air outside the conduit 16. Third section 72 may be integrally formed of one piece, or formed in multiple pieces and subsequently joined.

The fourth section of the housing 12 is the mouthpiece 32, which has a generally cylindrical portion 54 which is telescopingly received within the open downstream end of the third generally cylindrical portion 74 (which also encloses the open end 20 of the conduit 16). The portion 54 is attached to an annular flange 56, which in turn is attached to the reduced diameter portion 58 which is formed into a user's mouth. The outer diameter of portion 54 is approximately equal to the diameter of inner surface 58 so as to provide a tight fit therebetween.

The housing 12 advantageously is formed of a plastic such as polyolefin, polyester, polypropylene, polyethylene, ABS, polycarbonate, or polyacrylate. The housing 12 may be manufactured by any suitable technique such as injection molding or blow molding.

FIG. 3A shows an alternative embodiment of an actuator and nozzle assembly 28a for the inhaler 10. In cross-sectional view on the horizontal plane illustrated in FIG. 3. The actuator and nozzle assembly 28a includes two opposed-spun discharge orifices 30a which are both fluidly connected to the bore 29a and which converge toward each other in the direction of the mouthpiece 36. Thus, depressing the cushion 18 so as to discharge a measured volume of medication into the bore 29a causes two opposed plumes to be emitted from the pair of orifices 30a. The plumes converge and impinge on each other upstream of the air inlet nozzle 34,

causing the aerosol to spread out, thereby aiding mixing of the aerosol with air. Advantageously, impingement of the two plumes also is creating swirling droplets, which enhances evaporation of propellant. It will be appreciated that for convenience of illustration, the bore 29a is shown as being elongated in the horizontal direction and orifices 30a are shown as being spaced apart in the horizontal plane. Advantageously, however, the bore 29a may simply be extended in the vertical direction and the orifices 30a vertically spaced apart and angled toward each other so as to achieve the desired convergence of the two plumes.

FIG. 4 depicts an alternative embodiment of an inhaler 10b in which the elongated air inlet 34 of inhaler 10 has been replaced by a discrete air inlet in the form of a hole 42a which is supported in the conduit 16 by a pair of hollow spokes 43a. In FIG. 4, parts identified by reference numerals having the letter "a" suffix denote parts analogous to those having the same reference numerals without the suffix in FIG. 3, which parts identified with identical reference numbers in FIGS. 3 and 4 denote identical parts. Thus, the hole 42a is analogous to the axial portion 42 of the air inlet 34, and the spokes 43a are analogous to the radial portion 43 of air inlet 34. The hole 42a includes a counter sunk 53 of a first diameter, and an outlet passage 50a of a second smaller diameter. The outlet passage 50a is generally counter with the conduit 16 and orientated so that air flowing outward therethrough is directed toward the nozzle orifice 30. The inverted passages of spokes 43a are connected to ambient air by a pair of holes 52a through the cylindrical portion 74a. In the

embodiment of the inhaler 10a shown in FIG. 4, there is an section of the housing underneath on the second section 64 of FIG. 5. Thus, the vanes 54 have been eliminated from the inhaler 10a. However, the auxiliary air inlets 46 are still present in the inhaler 10a to provide a boundary layer air flow along the lower wall of the cavities 16a.

FIGS. 5 and 6 illustrate yet another embodiment of an inhaler in accordance with the principles of the present invention. FIG. 5 schematically depicts a horizontal cross section analogous to FIG. 3, showing an inhaler 10b in which the aerosol plume is directed away from the user so that the aerosol must reverse direction before being inspired. FIG. 6 schematically depicts a vertical cross section of the inhaler 10b. Again, like parts are denoted by like reference numerals, while analogous parts are denoted by the letter "b" suffix. The inhaler 10b includes a housing 12b defining a conduit 14b which has a first closed end defined by an end wall 90 and a second open end defined by a mouthpiece portion 22b adapted to be inserted into a user's mouth. The conduit 14b has a first larger internal cross sectional area over the majority of its length, narrowing to a second smaller internal cross sectional area at the mouthpiece portion 22b. The housing further includes a receptacle portion 24b which penetrates into the conduit 14b at a location between the end wall 90 and the mouthpiece portion 22b. The receptacle portion 24b receives a standard pressurized canister (not shown). The housing 12b further includes an actuator and nozzle assembly 28 arranged at the bottom end of receptacle portion 24b

such that the hollow nozzle stem of the canister may be inserted into a bore 23 of the actuator and nozzle assembly 28. The details of the actuator and nozzle assembly 28 have already been described in connection with FIG. 3. The nozzle discharge orifice 30 is oriented so as to direct an aerosol plume toward the end wall 90.

The inhaler 10b includes an internal conduit 92 which is coaxially disposed with the conduit 14b. The internal conduit 92 has an open end 94 spaced from and adjacent the end wall 90, and a closed end 96 recessed from the end wall 90 and defined by an end wall 34b which supports the actuator and nozzle assembly 28. The inhaler further includes an air tube 34b attached to the end wall 90 and coaxially disposed within the conduit 14b. The air tube 34b therefore part way into the inner conduit 92 toward the nozzle discharge orifice 30. The inlet 32b of air tube 34b is connected to ambient air outside the conduit 12b by a hole 98 through end wall 90. The outlet 36b of air tube 34b is in opposing relation to the orifice 30. Aerosol emitted from the orifice 30 causes loss the interior of inner conduit 92 and generally toward the end wall 90 of outer conduit 14b. Inhalation of the user through the mouthpiece 22b causes air to enter through hole 98 into air tube 34b and out the outlet 36b toward the plume. The plume and the air jet from air tube 34b mean, causing the plume to flow down and around an within inner conduit 92. Continued inhalation by the user causes the dispersed aerosol to exit through the open end 94 of inner conduit 92, and then reverse direction to flow through the space between the inner conduit 92 and the outer conduit 14b, and thence through the mouthpiece 22b.

Thus, the aerosol travels a portion of the length of conduit 14b twice, thereby increasing residence time of the aerosol within the device before exiting the mouthpiece 22b. This leads to more complete suspension of liquid propellant. Furthermore, the flow reversal insures that the velocity of the aerosol exiting the mouthpiece will be substantially equal to the velocity of the user's inspired breath, reducing the problems of impaction in the mouth and throat.

FIG. 7 depicts yet another embodiment of the invention providing automatic actuation of the canister to discharge a dose of medication in response to, and synchronized with, the user's inspiratory effort. An inhaler 10c includes a housing 12c having a conduit 14c within which an aerosol plume is created for inhalation by the user. The conduit 14c is shown to include the air tube 34 and the auxiliary air inlets 46. It may also include the vanes 54 of inhaler 10. Alternatively, the conduit 14c may be a simple straight duct with an open end for the exit of aerosolized medication. Thus, with the exception that the conduit 14c must adapted to provide fluid communication with a canister 15Z in housing 12c as discussed below, the details of the conduit 14c are not important to an understanding of the breath-synchronization features of the invention.

The housing 12c further includes a receptacle portion 24c which is connected to the conduit 14c. The receptacle portion 24c comprises a generally cylindrical sleeve having a longitudinal axis 25B which is oriented at an oblique angle to the longitudinal axis of the conduit 14c. A canister 15 resides within the receptacle

portion 24c with its longitudinal axis aligned with the longitudinal axis of the receptacle portion 24c. Disposed between the receptacle portion 24c and the canister 15 is an inner sleeve 100. The inner sleeve 100 has an open top end 102 through which the canister 15 may be inserted, and an open bottom end 104 which is constructed such that the canister 15 cannot go through it but which nevertheless provides the hollow stem 19 of the canister to be inserted into the bore 23 of actuator and nozzle assembly 28. More specifically, the sleeve 100 adjacent bottom end 104 has inwardly extending ledges 105 which abut the cap portion 106 of the canister. The canister 15 is shiftable within inner sleeve along the direction defined by the longitudinal axis 25B of receptacle portion 24c so as to permit the canister to be depressed toward the actuator and nozzle assembly 28 in order to actuate the canister's metering valve.

The inner sleeve 100 is also shiftable within the receptacle portion 24c along the direction of axis 25B for the purpose of placing the canister 15 in a cocked position ready to be actuated. The receptacle portion 24c has four longitudinal slots 110 circumferentially spaced apart about 90 degrees, one of which receives a pair of diametrically opposite legs or ears 112 extending outwardly from the outer surface of inner sleeve 100. Alternatively, the receptacle portion 24c may have only two slots 110 spaced 180 degrees apart and receiving the legs 112. Thus, as the inner sleeve slides longitudinally within receptacle portion 24c, the legs 112 slide longitudinally within the respective slots 110.

The inhaler includes a generally cylindrical cam ring 114 which fits over the outside of receptacle portion 14c. The cam ring 114 has an annular flange 116 at its lower end which extends outward beyond the outer surface of the housing so as to facilitate gripping of the cam ring 114 by the user's hand. The inner surface 118 of ring 114 has a pair of circumferentially extending recesses or cam tracks 120 formed thereon approximately 180 degrees apart which extend longitudinally upward to the open top end 122 of cam ring 114. Each cam track 120 presents a generally helical surface 124 in facing relationship with one of the lugs 112 protruding outwardly from the lower sleeve 100 through slots 110. Thus, starting with the cam ring 114 in a position in which each lug 112 is in contact with the lowermost portion of the respective cam track 120 (i.e., that portion of cam track 120 which is furthest from the top end 122 of cam ring 114), rotation of the cam ring 114 through the set defined by the cam tracks 120 causes the lugs 112 to ride along the helical surfaces 124 and thereby upwardly advance the inner sleeve 100 in the longitudinal direction toward the top end 122.

This upward movement of the inner sleeve 100 draws the canister 18 upward by virtue of the hedges 102. Resisting this upward movement of the canister 18 is a compression spring 126. The spring 126 is attached to the inner surface of a removable end cap 128 which surrounds the top end 130 of the receptacle portion 14c and the top end 122 of the cam ring 114 to completely enclose the canister 18 in the housing. When the end cap 128 is thus installed, the spring 126 bears against the end

of the canister 18, biasing the canister downward toward the actuator and nozzle assembly 26. With nothing to impede the downward movement of the canister 18, the spring 126 would move the canister downward until the discharge stem 19 were fully depressed into the canister so as to cause discharge of a metered volume of the canister contents. However, the inhaler 10c includes a mechanism which engages the canister to prevent this downward movement, with the mechanism being responsive to an inspiratory effort of a user counted on the open end of the mouthpiece 14a so as to disengage from the canister during the user's inhalation to allow the spring 126 to move the canister into its discharge position.

To these ends, the inhaler 10c includes a plate assembly 132 which is moveable relative to the canister 18 along an axis 134 generally normal to the longitudinal axis 108. The plate assembly 132 includes a circular disc 136 having a shaft 138 extending centrally therethrough coaxial with axis 134 and projecting outward from both sides of the disc 136. A first portion 140 of the shaft 138 projecting from the side of disc 136 remote from the canister engages a recess 142 in a wall 144 of the housing, the recess 142 guiding the movement of the plate assembly 132 along axis 134. A second portion 146 of shaft 138 projecting from the side of disc 136 facing the canister extends through an opening 148 in receptacle portion 14a, terminating at an enlarged head end 150. A compression spring 152 is captive between the head end 150 and the wall of the receptacle portion 14c, biasing the plate assembly 132 toward the canister 18.

A flatted trigger 154 is attached to the head end 150. The trigger 154 has two spaced-apart parallel prongs 156 (FIG. 8) which extend along the direction of axis 134 to approximately the longitudinal axis 108 of the receptacle portion 14c. The prongs 156 are spaced apart by a distance D which is slightly smaller than the diameter of the canister neck 158 from which the discharge stem 19 protrudes, as shown schematically in FIG. 8. Thus, when the plate assembly 132 is fully extended toward the canister 18, the canister neck 158 contacts inner edge portions 160 of the prong 156, as facilitated by the slanted regions in FIG. 8. However, when the plate assembly 132 is withdrawn along axis 134 away from the canister 18, the canister neck 158 clears the prongs 156 so that movement of the canister 18 toward the actuator 26 is permitted. The prongs 156 include portions 157 which slope gently away from the canister neck 158 in the direction along axis 134 toward the canister. The portions 157 reduce the amount of force required for disengagement of the trigger 154 from the canister neck 158.

Movement of the plate assembly 132 in the direction away from the canister is responsive to air pressure within a variable-volume chamber 162 within the housing. The chamber 162 is defined by the disc 136, the housing wall 144, and a flexible diaphragm 164 which connects the disc 136 to the wall 144 in a substantially air-tight manner. Advantageously, the diaphragm 164 includes a circular portion 166 which lies against the side of disc 136 facing the canister 18, and a ribbon 168 which depends from the outer edge of the circular portion 166 and attaches to the housing

wall 144. Further advantageously, the housing wall 144 comprises a removable cover 170 of the housing, and an edge of the ribbon 168 is attached to the housing by being sandwiched between the cover 170 and the remainder of the housing. The circular portion 166 of diaphragm 164 includes a central hole through which the shaft 138 extends and which tightly surrounds the shaft 138 to provide a substantially air-tight seal therebetween.

The moveable cover 170 includes a recess 172 facing the disc 136 which aligns with a passage 174 formed in a sidewall 176 of the housing. The passage 174 extends toward the open end 30c of conduit 14c. The conduit 14c is formed in at least two sections, a first generally cylindrical section 42c which includes the sidewall 176 and is connected to the end wall 34c through which the nozzle orifice 30 extends, and a second generally cylindrical section 54c which includes the air tube 36 and which connects to the first section 42c. The passage 174 terminates at the end of first section 42c which connects to second section 54c. A passage 178 through a sidewall 180 of the second section 54c is tightly connected with and forms an extension of passage 174. The passage 178 extends from the internal passage 182 of the air tube 36. A second 184 is inserted into the air tube passage 182. The magnet 134 includes a magnetic portion or dowel 186. Air passages 188 extend through the second wall in the vicinity of the dowel 186. The second 184 is disposed in passage 182 such that there are passages 182 align with the passage 178. Thus, fluid communication is provided between the variable chamber 162

and the variable-volume chamber 162 by air passages 173, passage 170 in inward section 76a, passage 174 in flow section 62a, and recess 172 in cover 170.

It will therefore be appreciated that when a user inhales through the open end 20c of conduit 16a, air is drawn from outside the conduit 16a through air inlet 34 into the primary air passage of the conduit 16a. This air has to flow through the venturi 184, and consequently a below-atmospheric air pressure exists in the venturi throat 186. This below-atmospheric air pressure is communicated to the chamber 162, such that the walls that the walls of the chamber 162 are subjected to a force proportional to the pressure difference between atmospheric pressure outside the chamber 162 and the below-atmospheric pressure inside the chamber 162. Consequently, air within the chamber 162 begins to evacuate the chamber 162 through recess 172, through passages 174 and 170, through passages 173, and into the venturi throat 186, and thence through the air inlet 34 into the primary air passage of the conduit 16a.

As the user continues to inhale through the conduit 16a, evacuation of air from the chamber 162 causes the volume in chamber 162 to decrease, with the result that the disc 136 and the shaft 133 begin to move toward the wall 144 against the force of the spring 152. Accordingly, the trigger 154 begins to move so as to disengage the passage 156 from the catcher notch 158. When the decrease in volume is sufficient to move the trigger 154 far enough to totally disengage the passage 156 from the notch 158, movement of the catcher 13 toward the actuator 26 is no longer

hampered, and the force of spring 126 moves the catcher downward so as to cause actuation of the catcher's contacting valve. A metered dose of aerosolized medication is thereby discharged from nozzle orifice 30 into the conduit 16a for inhalation by the user.

After the inhaler 10c has been actuated to dispense a dose of medication, it must be recocked so that it is ready to be discharged again. To this end, the user grasps the ring 114 and moves it with respect to the housing 12c through the arc defined by the slot tracks 120. This causes the lower shoes 100 and catcher 13 to be lifted upward against the force of spring 126. When the catcher 13 is raised upwardly sufficiently to allow the trigger 154 to clear the catcher notch 158, the spring 152 urges the trigger 154 toward the catcher 13 so that the trigger 154 once again is in a fully extended position to engage the catcher notch 158. The user then extends the cam ring 114 back to its starting position to lower the catcher 13, whereupon the catcher notch 158 seats against the passage 156 of the trigger 154. The inhaler 10c is then ready to be used again.

It will be appreciated that the breath-synchronization features described above provide an inhaler in which discharge of medication is automatically responsive to the user's inspiratory effort, so that the user does not have to carefully coordinate manual depression of a canister with the inhalation. Furthermore, discharge of medication does not occur instantaneously upon the user beginning to inhale on the open end of the device, but rather is somewhat delayed until the volume of chamber 162

has decreased enough to cause actuation. It will also be appreciated that the degree of time delay between initiation of a breath and actuation is dependent on a number of factors, the primary factors being the cross-sectional area of the chamber 162 and the spring constant of the spring 152, since a discharge of medication requires a certain minimum travel of the catcher 13 to cause the discharge nozzle 17 to be fully depressed, and the travel is proportional to the pressure difference across the chamber times its cross-sectional area divided by the spring constant. Accordingly, the inhaler 10c may be designed with appropriate selection of these factors so as to achieve actuation of the catcher 13 near the peak of a user's inhalation.

Moreover, the inhaler 10c provides breath-responsive actuation of the catcher 13 which automatically adjusts to the user's rate of inhalation to discharge the medication near the peak of the inhalation, i.e., near the point at which 50 percent of the volume which the user will eventually inspire with a full inhalation has been inspired. For instance, if a user with normal lung function inhales quickly through the open end 20c, air will be evacuated from the chamber 162 more rapidly so as to achieve actuation in a relatively short time. Conversely, if a user with impaired lung function inhales slowly through the open end 20c, air will be evacuated more slowly from chamber 162 so as to achieve actuation in a relatively longer time.

The inhaler 10c further includes an adjustment screw 190 which extends through the housing 12c into the passage 174 to form a restriction within passage 174. By moving the screw 190 one direction, the screw 190 extends further

into passage 174 to increase the restriction, and by moving the screw 190 the opposite direction, it serves to decrease the restriction. Thus, the timing of actuation of the catcher 13 in relation to a particular patient's inhalation may be varied by adjusting the screw 190. Varying the screw position results in a variation in pressure difference across the walls of the variable-volume chamber 162 at a given flow rate out the open end 20c of conduit 16a. Thus, for a given flow rate out the open end 20c of conduit 16a, turning the screw 190 to increase the restriction of passage 174 will increase the time period required to evacuate the chamber 162 sufficiently to cause actuation, whereas turning the screw 190 to decrease the restriction will decrease such time period.

FIG. 9 depicts a schematically yet another embodiment of an inhaler having features for automatic breath actuation of discharge. In this embodiment, the locked trigger 154 is eliminated and the diaphragm plates normally 132 is replaced by a resiliently compressible bellows 200 which is disposed between a front end 202 of the housing 12ee shown and the catcher notch 158. The bellows 200 itself acts as the restraint which keeps the catcher in a pre-actuated position, the bellows being compressed by air pressure into a position permitting the catcher to move into a discharge position.

The bellows 200 is advantageously made of stainless steel and has a front end wall 204 at the end adjacent the catcher notch 158, the end wall 204 being integrally formed with the accordion-folded side wall 206. The bellows 200 has a

second end wall 206 at the end adjacent the housing wall 202, the end wall 208 also being integrally formed with the side wall 206. The second end wall 208 is pierced by a tube or nozzle 210 which establishes an air passage into the interior of the bellows 200. The nozzle 210 subsequently is a stainless steel tube similar to a hypodermic needle and is integrally affixed at one end to the end wall 208 by welding or other suitable techniques. The free end 212 of the nozzle 210 connects in sealed relation with a tube 213 to the throat 214 of a venturi 216. The venturi 216 is disposed within a tube 218 which extends from an inlet end 220 which draws air from outside the inhaler housing, to an exit end 222 which is arranged within the conduit (not shown) opposite the nozzle discharge orifice 30. The tube 218 and venturi 216 may also be formed of stainless steel.

A supportwhisker platform 224 is attached to the blind end wall 204 of the bellows 200. The supportwhisker platform 224 contacts the canister neck 158 throughout the range of motion undergone by the canister in moving from a rest or ready position to a discharge position. The bellows 200, via the supportwhisker platform 224, exerts a spring force on the canister neck 158. The force of the bellows 200 acts in a direction tending to move the canister neck 158 away from the nozzle 26. Additionally, as is well known, the canister 18 contains an internal spring (not shown) which acts between the canister body and the hollow canister stem 19 in a direction tending to move the canister 18 away from the nozzle 26. The spring constant of the bellows 200 is selected such that the sum of the spring force

exerted by the bellows 200 and the force exerted by the internal spring is slightly greater than the force exerted by the spring 126 (FIG. 7) which exerts a force on the end of the canister 18 in the direction as tend to move the canister 18 toward the nozzle 26 into its discharge position. Thus, at rest, with atmospheric pressure acting both inside and outside the bellows 200, the bellows 200 and internal spring overcomes the force of the spring 126 and thereby keep the canister 18 in a ready position preventing discharge of medication therefrom.

However, when a user inhales through the nozzle (see discussion of the inhaler, air is drawn through the tube 218, as previously described in connection with the inhaler 10a, which creates a low pressure within the throat 214 of venturi 216. This low pressure is communicated via the connection tube 213 and nozzle 210 to the interior of the bellows 200. As a result, the pressure within the bellows 200 is less than the atmospheric pressure which surrounds the outside of the bellows 200, and therefore there is an air pressure force exerted on the blind end wall 204 in the direction toward the housing wall 202. The sum of this air pressure force and the force of the spring 126 exceeds the spring force exerted by the bellows 200 and the canister internal spring, causing the blind end wall 204 of bellows 200 to be compressed toward the housing wall 202. By virtue of the force exerted on the canister 18 by the spring 126, the canister follows the end wall 204. With continued evacuation of air from the bellows 200, the canister 18 is moved into its discharge position. Once the user completes his inhalation and air flow through the venturi 216

ceases, air pressure is again equalized inside and outside the bellows 200, and the bellows 200 returns to its starting position, the forces of the bellows 200 and internal spring forcing the canister 18 back upward against the force of the spring 126 into the ready position. Thus, with the breath-actuation system depicted in FIG. 9, there is no need for a separate cocking system.

The bellows 200 preferably has a spring constant of about 1 pound per inch to about 15 pounds per inch, and a cross-sectional area of about 0.2 to about 0.75 square inch. Thus, a pressure differential of about one pound per square inch across the bellows 200 is sufficient to compress the bellows 200 by an amount of about 0.020 inch to about 0.080 inch. With a standard canister 18, only about 0.040 inch of relative movement is required between the discharge stem 19 and the canister body in order to ensure discharge. Accordingly, the venturi 216 need be closed to create a gap therewith with the throat 214 of about one pound per square inch.

While the present invention has been illustrated by a description of various embodiments and while these embodiments have been described in considerable detail, it is not the intention of the applicants to restrict or in any way limit the scope of the appended claims to such detail. Additional advantages and modifications will readily appear to those skilled in the art. For example, while the inhalers which are illustrated and described have the venturi tube in communication with ambient air via a passage through the mouth wall, the venturi tube may alternatively draw air through one of the auxiliary air inlets 48 in the end wall 34, or

through any arrangement having the venturi inlet outside the primary air passage defined by the inhaler conduit. Additionally, the stainless steel bellows 200 of FIG. 8 may advantageously be used in the inhaler configuration depicted in FIG. 7, with the bellows 200 replacing the piston assembly 132 and the blind end wall 204 of the bellows 200 being attached to the finger trigger 154, and the spring 152 being eliminated by virtue of the resiliency of the bellows 200. The invention in its broader aspects is therefore not limited to the specific details, representative apparatus and methods, and illustrative examples shown and described. Accordingly, departures may be made from such details without departing from the spirit or scope of applicant's general inventive concept.

With reference to the use of the word(s) "comprise" or "comprises" or "comprising" in the foregoing description and/or in the following claims, unless the context requires otherwise, those words are used on the basis and clear understanding that they are to be interpreted inclusively, rather than exclusively, and that each of those words is to be so interpreted in construing the foregoing description and/or the following claims.

The claims defining the invention are as follows:

1. An aerosol flow control apparatus providing automatic discharge of medicament responsive to an inspiratory effort of a user, the apparatus comprising:

a pressurized canister of medicament including a canister body and a hollow discharge stem which is movable with respect to the canister body between an inoperative position in which discharge of medication is prevented and an operative position in which medication is discharged through the discharge stem,

a housing adapted to support the canister and provide movement thereof between a first position in which the discharge stem is in the inoperative position and a second position in which the discharge stem is in the operative position, the housing further defining a primary air passage including an outlet through which a user can inhale and also defining a secondary air passage extending between the primary air passage and ambient air outside the primary air passage, the secondary air passage including a manual bowing a throat;

a variable-volume device supported within the housing and including a wall which is movable with respect to the housing, the variable-volume device defining a variable-volume chamber therein in fluid communication with the vented throat;

a canister restraint affixed to the movable wall of the variable-volume device, the canister restraint being movable with the movable wall from a rest position in which the canister is in the first position and relative movement between the canister body and discharge stem is prevented, to a discharge position in which the canister is free to move into the second position,

a resilient member which urges the canister into the second position upon movement of the canister restraint into its discharge position; and

the variable-volume chamber being in fluid communication with the primary air passage, whereby inhalation of a user through the outlet causes air to be drawn through the vented throat thereby creating a low pressure in the throat which is communicated to the variable-volume chamber, the low pressure causing air to be evacuated from the chamber and thereby cause the movable wall to move the canister restraint into the discharge position.

2. The aerosol flow control apparatus of claim 1, wherein the vented throat is connected to the chamber by a third air passage within the housing, and further comprising an adjustment device which may be selectively positioned to selectively vary the flow rate

through the third air passage at a given flow rate through the primary air passage, thereby varying the timing of medication discharge in relation to the inhalation cycle of a user.

3. The aerosol flow control apparatus of claim 1, wherein the variable-volume device comprises a piston which is sealingly connected to a wall of the housing by a flexible diaphragm, and the canister restraint includes a member which is attached to the piston and which in the rest position intrudes into the path travelled by the canister between the first and second positions so as to prevent the canister from moving into the second position, evacuation of air from within the chamber of the variable-volume device causing the piston to move toward the housing wall and thereby withdraw the member into the discharge position permitting the canister to move into the second position.

4. The aerosol flow control apparatus of claim 1, wherein the housing comprises a main body portion which receives the canister, and an end cap which covers the end of the canister opposite from the end with the discharge stem and which engages the main body portion to prevent inadvertent removal therefrom, the resilient member comprising a compression spring between an inner surface of the end cap and the canister such that the spring bears against the canister when the end cap is engaged with the main body portion.

5. The aerosol flow control apparatus of claim 2, wherein the main body portion includes a generally cylindrical receptacle having a longitudinal axis and defining a generally cylindrical recess in which the canister resides, and further comprising a cocking device including:

an inner sleeve which surrounds the canister within the receptacle, the inner sleeve and canister being slidable together as a unit within the receptacle along the longitudinal axis, the inner sleeve further including at least one pin extending outwardly from an outer surface thereof through a slot in the receptacle; and

a cocking ring which surrounds the receptacle and has a surface which engages the at least one pin, the cocking ring being movable with respect to the receptacle so as to move the pin in the direction defined by the longitudinal axis toward the end cap so as to draw the inner sleeve and canister upward and thereby move the canister into a cocked position which permits the canister restraint to move into its rest position, thereby readying the apparatus for actuation in response to the inspiratory effort of a user.

6. The aerosol flow control apparatus of claim 1, wherein the variable-volume device comprises a resiliently compressible bellows, the bellows being disposed between a wall of the canister and a wall of the housing which faces the canister such, the movable wall being an end wall of the bellows, the canister restraint being affixed to the end wall and contacting the canister such, the bellows being compressible toward the housing wall in a direction substantially parallel to the direction in which the canister moves from the first position to the second position, the bellows being adapted to exert a spring force on the canister tending to urge the canister toward the first position, the spring force exceeding the force exerted on the canister by the resilient member by a predetermined amount which is selected such that when a user inhales through the outlet of the housing, the pressure force exerted on the end wall of the bellows by the difference between atmospheric pressure outside the bellows and the low pressure inside the bellows exceeds the predetermined amount, thereby causing the end wall to compress the bellows toward the housing wall and move the canister restraint into the discharge position such that the canister is moved into the second position by the resilient member.

7. A method for delivering a dose of medication using an aerosol delivery apparatus which houses a medication-containing canister having a canister body and a hollow outlet stem movable with respect to the canister body between an inoperative position in which discharge of medication is prevented and an operative position in which medication is discharged through the outlet stem, with the canister being moveable within the apparatus between a first position in which the outlet stem is in the inoperative position and a second position in which the outlet stem is in the operative position, the apparatus including a housing defining a primary air passage having an outlet through which a user can inhale and a secondary air passage, the synchronizing discharge of medication from the canister with an inspiratory effort of a user through the outlet, the method comprising:

placing the canister in the first position;

preventing movement of the canister into the second position by a canister restraint which engages the canister to prevent said movement and which is moveable in response to below-atmospheric air pressure within a variable-volume device arranged within the housing, the variable-volume device defining an air chamber therein, the canister restraint being moveable to permit the canister to move into the second position upon a predetermined decrease in volume of the air chamber;

urging the canister toward the second position;

upon a user inhaling through the outlet, drawing air through a secondary air passage arranged within the housing, the secondary air passage extending from the primary air passage to ambient air outside the primary air passage, the secondary air passage including a vented bowing a throat; and

at least during the drawing step, providing fluid communication between the throat portion of the vented of the secondary air passage and the variable-volume air chamber so as to communicate a below-atmospheric air pressure created by the vented to the air chamber and thereby create the chamber volume to decrease, whereby the canister restraint moves to permit said movement of the canister into the second position to discharge medication when the predetermined decrease in chamber volume is reached.

8. The method of claim 7 wherein the throat portion of the vented has a reduced cross-sectional flow area relative to the remainder of the secondary air passage such that the air pressure in the throat portion is lower than the air pressure in the remainder of the secondary air passage when air is flowing therethrough.

DATED this 14 day of July 2004

SYSTEMIC PULMONARY DELIVERY, LTD.
By its Patent Attorneys,
E. F. WELLINGTON & CO.,

Brian Wellington



FIG.1

FIG.2



FIG.3

FIG.3A



FIG.4



FIG.5



FIG.6



FIG.8

FIG.7



FIG.9